



# HP Portable Bucket Pump

Alemite's HP Portable Pump is a robust mini pump designed to handle chassis, viscous, or fibrous lubricants up to NLGI #3. This lightweight, durable pump provides high pressure, low volume delivery, and smooth operation, making it an ideal choice as a stationary centralized lubrication pump or as portable pump in a variety of industrial and mining applications. The HP Portable pump fits 35 lb. (16 kg.) buckets in standard steel or non-standard plastic sizes. \*

- Rugged all-steel construction for durability in the harshest industrial and mining environments
- Case-hardened mechanical directional valves for long life and trouble-free operation
- Self lubricating metal-to-metal seals for longer life; no elastomer seals to replace
- High ratio for pumping heavy fluids in cold conditions, long runs, and high back pressure applications
- Double acting operation for smooth transfer and displacement of fluids
- Short exhaust path for quick and positive shifting resulting in faster pumping
- Lightweight portability for an easy, cost-effective means of providing lubrication to remote areas where automatic lubrication is not feasible

Model	Ratio	Delivery/Minute lbs. (kg)	Maximum Pressure		Fits Drum lbs. (kg)	Includes		Inlet	Outlet
			PSI	Bar		Follower	Cover		
711-R	40:1	0.75 (0.33)	6,000	414	35 lb (16)	337665	338411	1/8"	1/4"
711-S**	40:1	0.75 (0.33)	6,000	414	35 lb (16)	337665	338166	1/8"	1/4"

\*Order the #340090 universal adapter for non-standard plastic buckets

\*\*711-S includes control valve (337854), 7' high pressure hose (317875-7), and swivel (52752).

## Markets/Applications

Mining, Industrial, Manufacturing, Automotive/Fleet, Mobile Lube Trucks, and Field/Plant Service Crews



167 Rowland Drive  
 Johnson City, TN 37601  
 Toll Free U.S.: 866-4-Alemite  
 Toll Free Canada: 800-267-8022  
 International: 803-802-0001  
 Fax U.S.: 800-648-3917  
 Fax Canada: 800-267-2880  
 Fax International: 803-802-0192  
 www.alemite.com

LT128 01/06

